

RO-BOOM 1800

- Heavy-duty oil containment boom

The design draws upon the traditional strong points of the RO-BOOM system i.e. individual air chambers, high quality construction, good stability and survivability. Although lighter, RO-BOOM 1800 is still significantly superior to other types of inflatable booms in terms of tensile strength, puncture resistance, abrasion resistance and tear resistance.

RO-BOOM 1800 will withstand the effects of sun, sea and oils, which destroy many booms made from other materials. The minimal storage volume of RO-BOOM simplifies the logistics of storing, loading and transporting significant quantities of boom.

Attachments, such as eyelets and brackets are made from stainless steel, AISI 316. The boom has moulded, inflatable chambers - the total free-board is approx. 0.60 m, and the overall height of the boom in inflated condition is approx. 1.50 m. The individual buoyancy chambers have separate air valves, which mean that in the unlikely case of puncture only one chamber will lose air, and not impair the integrity of the boom. The smooth surface of the deflated boom makes cleaning easier - several types of oil do not stick to the boom at all.

Deployment is very rapid using our high capacity air blowers.



RO-BOOM 1800 was introduced to meet the demand for a large robust boom.

RO-BOOM 1800



Advantages of RO-BOOM 1800:

- A durable boom resistant to abrasion, oils and sunlight
- Individual air chambers for reliability and security
- Lies flat when deflated for easy storage and cleaning
- Stainless steel and hot galvanized components
- High visibility stripe
- Reels, containers and bags available
- Rapid deployment
- Third layer of fabric at the chain attachment area for added strength

TECHNICAL DATA

RO-BOOM 1800 oil containment boom is manufactured from heavy-duty Neoprene rubber with a Hypalon external skin. This unique one-piece moulded composite construction has complete cross vulcanisation of rubber and reinforcing fabrics. The construction is seamless, it has high abrasion resistance, peel resistance and tensile strength. RO-BOOM lies completely flat when deflated allowing for easy cleaning and storage. The individual air chambers provide high integrity. RO-BOOM is fitted with stainless steel fittings and a hot galvanized ballast/tension chain. Internal fibreglass rods secured with stainless steel brackets. These rods ensure optimum skirt profile under tow. ASTM quick connectors are fitted as standard.

Overall width, deflated:	1.80 m / 71 in
Standard section lengths:	50, 100, 200 m / 164, 328, 656 ft
Operational freeboard:	0.60 m / 23 in
Operational depth of skirt:	0.90 m / 35 in
Operational weight (inclusive of chain):	13.5 kg/m / 9.0 lbs/ft
Buoyancy chamber length:	4.5 m / 177 in
Section connector:	ASTM or Stainless steel hinge or pin
Standard colour:	Black with high visibility yellow marker stripes
Tensile strength of boom wall:	315 N/mm / 1,795 lbs/in
Breaking load of chain:	200 kN
Operational temperature range:	-20°C to +70°C
Stored temperature range:	-40°C to +70°C

RO-BOOM 1800

- Contact one of the offices below for further information



All information is subject to change, and pictures are for illustration purposes only, and not necessarily correct.

www.ro-cleandesmi.com



Head Office
RO-CLEAN DESMI A/S
Hestehaven 61
DK-5260 Odense S
Phone: + 45 65 91 02 01
Fax: + 45 65 48 16 15
E-mail: Denmark.ro-clean@desmi.com

U.S.A. Office,
APPLIED FABRIC TECHNOLOGIES INC
PO Box 575,
227 Thorn Ave,
Orchard Park, NY 14127
Tel: +1 716 662 0632
Fax: +1 716 662 0306
E-mail: bestboom@afti.com

U.K. Office
RO-CLEAN DESMI LTD.
Unit 24, Shamrock Quay
William Street
Southampton, SO14 5QL
Tel. +44 23 80829751
Fax. +44 23 80339190
E-mail: uk.ro-clean@desmi.com

Latin America Office
RO-CLEAN DESMI LATINOAMERICA S.A.
Calle Amagasi del Inca E14-68 y 2°
Transversal
Edificio RO-CLEAN DESMI - PB
Quito-Ecuador
Tel.: +593 2 326 1939
Fax: +593 2 326 4844
E-mail: Latinoamerica.ro-clean@desmi.com

Asia Office
RO-CLEAN DESMI ASIA
50/F Menara BCA
Jl. MH. Thamrin No. 1
Jakarta 13010 Indonesia
Tel: +62 21 2358 4468
Fax: +62 21 2358 4401
E-mail: asia.ro-clean@desmi.com