

SEAMOP

- Vertical rope mop skimmers

The continuous mop loops are circulated across the water surface and through the hanging wringer unit. The oil on the water sticks to the oleophilic mop surface and is removed within the SEAMOP. Recovered oil is drained or pumped to storage. The 3060, 5060 models are offered with a suction pump working from the deck or may be fitted with the DOP-160 pump. The SEAMOP 4090 and 8090 models offer a number of features including remote adjustment of roller pressure and opening (for feeding mop/access) and can be gravity drained or fitted with the DOP-250 pump. The larger models are also delivered with a drip tray as standard. The SEAMOPS are most efficient with light, medium and emulsified oils. Heavy oil may be recovered with heat or steam injection. SEAMOPS have been proven in a number of oil spills, performance has been witnessed by Lloyds Register.



The SEAMOP is a highly efficient mop skimmer that is ideal for choppy or open waters where high collection efficiency is required.

SEAMOP



Advantages of SEAMOP:

- Hanging mop skimmers with viscous oils, tar balls, and high efficiency
- Four models for inshore, coastal and offshore environments
- Choice of recovered oil transfer pumps or gravity drain
- Transfer pumps may be dismantled and used independently
- Larger models are fitted with remotely controlled roller tension
- SEAMOP can be delivered with hydraulic knuckle cranes or lifting davit

TECHNICAL DATA

	SEAMOP 3060	SEAMOP 5060	SEAMOP 4090	SEAMOP 8090
Nameplate capacity:	10 m ³ per hour / 44 US gpm	15 m ³ per hour / 66 US gpm	30 m ³ per hour / 132 US gpm	70 m ³ per hour / 308 US gpm
Mops:	3 x 6 in	5 x 6 in	4 x 9 in	8 x 9 in
Mop speed:	Max 40 metres / 130 ft per min	Max 40 metres / 130 ft per min	Max 40 metres / 130 ft per min	Max 40 metres / 130 ft per min
Operating height:	1 to 1.5 metres / 3 to 5 ft	1 to 1.5 metres / 3 to 5 ft	3 to 4 metres / 10 to 13 ft	3 to 4 metres / 10 to 13 ft
Roller tension:	Spring	Spring	Hydraulic	Hydraulic
Max hydraulic demand:	7.5 litres / 2 US gpm / min 100 bar / 1450 psi	7.5 litres / 2 US gpm / min 100 bar / 1450 psi	25 litres / 7 US gpm / min 120 bar / 1740 psi	25 litres / 7 US gpm / min 120 bar / 1740 psi
Hydraulic hose connections (excl. pump):	2 x ½ in	2 x ½ in	2 x ½ in 2 x 3/8 in	2 x ½ in 2 x 3/8 in
Dimensions:	0.63 x 0.63 x 0.48 m / 25 x 25 x 19 in	0.63 x 1.0 x 0.48 m / 25 x 39 x 19 in	1.53 x 1.2 x 1.3 m / 60 x 47 x 51 in	1.63 x 1.5 x 1.63 m / 64 x 59 x 64 in
Weight with hoses:	Dry 112 kg / 247 lbs Wet 180 kg / 397 lbs	Dry 180 kg / 397 lbs	Dry 590 kg / 1,300 lbs Wet 1,150 kg / 2,535 lbs with DOP-160 pump	Dry 900 kg / 1,984 lbs with DOP-250 pump
Suction drain connection:	3 in	3 in	3 in	6 in
Pump/suction option:	Spate 75C or DOP-160	Spate 75C or DOP-160	DOP-160	DOP-250 DUAL

- Contact one of the offices below for further information



All information is subject to change, and pictures are for illustration purposes only, and not necessarily correct.

SEAMOP

www.ro-cleandesmi.com



Head Office
RO-CLEAN DESMI A/S
Hestehaven 61
DK-5260 Odense S
Phone: + 45 65 91 02 01
Fax: + 45 65 48 16 15
E-mail: Denmark.ro-clean@desmi.com

U.S.A. Office,
APPLIED FABRIC TECHNOLOGIES INC
PO Box 575,
227 Thorn Ave,
Orchard Park, NY 14127
Tel: +1 716 662 0632
Fax: +1 716 662 0306
E-mail: bestboom@afti.com

U.K. Office
RO-CLEAN DESMI LTD.
Unit 24, Shamrock Quay
William Street
Southampton, SO14 5QL
Tel. +44 23 80829751
Fax. +44 23 80339190
E-mail: uk.ro-clean@desmi.com

Latin America Office
RO-CLEAN DESMI LATINOAMERICA S.A.
Calle Amagasi del Inca E14-68 y 2°
Transversal
Edificio RO-CLEAN DESMI - PB
Quito-Ecuador
Tel.: +593 2 326 1939
Fax: +593 2 326 4844
E-mail: Latinoamerica.ro-clean@desmi.com

Asia Office
RO-CLEAN DESMI ASIA
50/F Menara BCA
Jl. MH. Thamrin No. 1
Jakarta 13010 Indonesia
Tel: +62 21 2358 4468
Fax: +62 21 2358 4401
E-mail: asia.ro-clean@desmi.com