

# HELIX SKIMMER

- A Powerful, innovative circular brush skimmer

The HELIX is a revolutionary circular brush skimmer. It has been known for some time that circular skimmers have some operational advantages over square or rectangular units – namely that the oil is able to flow freely onto the collection surface from any angle. This is especially important with thick and viscous oils which are unable to flow. RO-CLEAN DESMI have invented a new brush drive mechanism that rotates on a curved stainless steel shaft enabling the brushes to “grab” the oil from any side of the skimmer and pull it into the pump. Power to rotate the brushes is provided by a hydraulic motor mounted with a gearbox, ensuring the heaviest of oils can be recovered. The HELIX skimmer is available supplied as a complete skimmer head fitted with the well-proven DOP pump in various sizes, alternatively it can be supplied as an adaptor to fit onto other skimmers. The large diameter brushes enable the HELIX to achieve high recovery rates.



The HELIX skimmer is a powerful brush skimmer in a revolutionary circular design to increase efficiency and total collection surface. The skimmer has a unique brush drive enabling it to collect the heaviest of oils.

**HELIX SKIMMER**



**Advantages of the HELIX:**

- 360 degree oil encounter rate
- High oil recovery rate
- Drive motor fitted with gearbox for high torque
- Suitable for a wide range of oils
- Large diameter brush wheels
- Lifting point and splash cover included
- Stand alone skimmer or adaptor for mounting on other models of weir skimmer
- Patent pending circular brush design

**TECHNICAL DATA**

Model	HELIX 160	HELIX 200	HELIX 250	HELIX 1000 MkIV
<b>Dimensions:</b>	1.65 x 1.85 x 0.8 m / 65 x 73 x 32 in	2.5 x 2.75 x 1.1 m / 98 x 108 x 43 in	2.1 x 2.35 x 1.1 m / 83 x 92 x 43 in	Dependant on skimmer it's mounted on
<b>Weight:</b>	180 kg	215 kg	230 kg	Dependant on skimmer it's mounted on
<b>Pump:</b>	DOP-160	DOP-200 DUAL	DOP-250 DUAL	N/A
<b>Max Pump Rate:</b>	30 m <sup>3</sup> per hr / 132 US gpm	66 m <sup>3</sup> per hr / 290 US gpm	125 m <sup>3</sup> per hr / 440 US gpm	N/A
<b>Operating Draught:</b>	0.4 m / 16 in	0.78 m / 30 in	1.15 m / 45 in	Dependant on skimmer it's mounted on
<b>Brush Discs:</b>	24 x 290 mm / 11.5 in diameter, bristle length 100 mm / 4 in	24 x 290 mm / 11.5 in diameter, bristle length 100 mm / 4 in	24 x 290 mm / 11.5 in diameter, bristle length 100 mm / 4 in	24 x 290 mm / 11.5 in diameter, bristle length 100 mm / 4 in
<b>Brush Assembly:</b>	1.3 m / 51 in diameter	1.3 m / 51 in diameter	1.3 m / 51 in diameter	1.3 m / 51 in diameter
<b>Brush Speed:</b>	35 rpm max	35 rpm max	35 rpm max	35 rpm max
<b>Main Frame:</b>	Sturdy aluminium marine grade	Sturdy aluminium marine grade	Sturdy aluminium marine grade	Sturdy aluminium marine grade
<b>Hydraulic Drive:</b>	8 cc hydraulic motor with worm gear	8 cc hydraulic motor with worm gear	8 cc hydraulic motor with worm gear	8 cc hydraulic motor with worm gear
<b>Gearbox:</b>	Fitted with 40:1 gearbox	Fitted with 40:1 gearbox	Fitted with 40:1 gearbox	Fitted with 40:1 gearbox
<b>Hydraulic Connections:</b>	Pump: 3/4 in P/R - 3/8 in Drain Helix: 1/2 in P/R - 3/8 in Drain	Pump: 3/4 in P/R - 3/8 in Drain Helix: 1/2 in P/R - 3/8 in Drain	Pump: 3/4 in P/R - 3/8 in Drain Helix: 1/2 in P/R - 3/8 in Drain	Pump: 3/4 in P/R - 3/8 in Drain Helix: 1/2 in P/R - 3/8 in Drain
<b>Hydraulic Demand:</b>	10 litres/min at 100 bar / 2.6 US gpm at 1,450 psi	10 litres/min at 100 bar / 2.6 US gpm at 1,450 psi	10 litres/min at 100 bar / 2.6 US gpm at 1,450 psi	10 litres/min at 100 bar / 2.6 US gpm at 1,450 psi



**HELIX SKIMMER**

**- Contact one of the offices below for further information**

All information is subject to change, and pictures are for illustration purposes only, and not necessarily correct.

**www.ro-cleandesmi.com**



**Head Office**  
RO-CLEAN DESMI A/S  
Hestehaven 61  
DK-5260 Odense S  
Phone: + 45 65 91 02 01  
Fax: + 45 65 48 16 15  
E-mail: Denmark.ro-clean@desmi.com

**U.S.A. Office,**  
APPLIED FABRIC TECHNOLOGIES INC  
PO Box 575,  
227 Thorn Ave,  
Orchard Park, NY 14127  
Tel: +1 716 662 0632  
Fax: +1 716 662 0306  
E-mail: bestboom@afti.com

**U.K. Office**  
RO-CLEAN DESMI LTD.  
Unit 24, Shamrock Quay  
William Street  
Southampton, SO14 5QL  
Tel. +44 23 80829751  
Fax. +44 23 80339190  
E-mail: uk.ro-clean@desmi.com

**Latin America Office**  
RO-CLEAN DESMI LATINOAMERICA S.A.  
Calle Amagasi del Inca E14-68 y 2°  
Transversal  
Edificio RO-CLEAN DESMI - PB  
Quito-Ecuador  
Tel.: +593 2 326 1939  
Fax: +593 2 326 4844  
E-mail: Latinoamerica.ro-clean@desmi.com

**Asia Office**  
RO-CLEAN DESMI ASIA  
50/F Menara BCA  
Jl. MH. Thamrin No. 1  
Jakarta 13010 Indonesia  
Tel: +62 21 2358 4468  
Fax: +62 21 2358 4401  
E-mail: asia.ro-clean@desmi.com