

# **MULTI-PURPOSE POWER PACK 2** - Versatile hydraulic power units

The MULTI-PURPOSE POWER PACKS from RO-CLEAN DE-SMI are extremely versatile units. Many of thse power packs are offered with two or more hydraulic circuits. Our oil spill products have been adapted to work with these power packs and therefore reduce the number of single function power packs to an absolute minimum.

This provides the operator with the most versatile equipment.

In addition, these units may reduce the overall investment of establishing an oil spill response capacity.

The power packs are designed for easy access to components, and have steel frames that are hot galvanised or epoxy painted.

The 25kW / 33 hp model is available with road wheels and tow bar or site wheels and handles for positioning by hand.

The 25, 50, 86 and 119 kW / 34, 68, 117 & 162 hp models are available with manual or electronic remote controls so the operator can place himself in the position to observe the activity – vastly improving safety!

RO-CLEAN DESMI manufacture a complete range of custom-built hose reels for storing all types of hose which we offer. N **MULTI-PURPOSE POWER PACK** 







Advantages of the MULTI-PUR-POSE POWER PACK:

- Diesel-hydraulic power packs from 3 kW to 119 kW for operation of a wide range of equipment
- Manual or electrical proportional flow control valves
- Remote control available for 25, 50 & 119 kW / 34, 67 & 115 hp versions
- All models fitted with fork lift channels
- Site or road wheels
- 25, 42, 50, 86, 119 kW Power Packs equipped with load sensing hydraulic control system (energy saving system)
- More than one reel can be present on each HOSE REEL
- Can be manufactured in stainless steel if this is beneficial
- Umbilical hose available to prevent the full hose having to be removed from the HOSE REEL.
  - Contact one of the offices below for further information

# 

### Issue no 1

Model	42 KW / 57 hp	50 kW /68 hp	86 kW / 117 hp	119 kW / 162 hp
Max total hydraulic flow & pressure:	160 lpm / 42 US gpm 210 bar / 3,045 psi	160 lpm / 42 US gpm 210 bar / 3,045 psi	180 lpm / 47.5 US gpm 210 bar / 3,045 psi	320 lpm / 84.5 US gpm 200 bar / 2,900 psi
No of circuits:	1 to 4	1 to 5	1 to 5	6
Oil Cooler:	Yes	Yes	Yes	30 kW
Starting options:	Electric / spring	Electric / spring	Electric / spring	Electric / spring
Standard hydraulic connection	<sup>3</sup> ⁄4" <sup>1⁄2</sup> " 3/8" drain	1″ ½″ 3/8″ drain	1" <sup>3</sup> ⁄4" <sup>1</sup> ⁄2" 3/8" drain	1″ ½″ 3/8″ drain
Frame finish:	Epoxy painted	Epoxy painted	Epoxy painted	Epoxy painted
Air blower (for boom inflation):	Optional	Optional	Optional	Optional
	Skid	Skid	Skid	Skid
Weight:	750 kg / 1,653 lbs	1100 kg / 2,425 lbs	1200 kg / 2,645 lbs	2200 kg / 4,850 lbs
Dimensions:	1.85 x 1.0 x 1.25 m	2.0 x 1.0 x 1.25 m	2.0 x 1.1 x 1.25 m	2.6 x 1.3 x 1.65 m
Silent engine avail- able	Yes	Yes	No	No

The 50 kW / 67 hp, 86 KW / 117 hp and 119 kW / 162 hp Multi-purpose power pack can be supplied with a hydraulic knuckle crane incorporated on the same skid frame. The DOP-250 DUAL vertical screw pump can be attached to the end of the knuckle crane for powered handling.

Additionally the crane may be used for a variety of purposes including skimmer handling. including skimmer handling.



2

## www.ro-cleandesmi.com

TECHNICAL DATA



Head Office RO-CLEAN DESMI A/S Hestehaven 61 DK-5260 Odense S Phone: + 45 65 91 02 01 Fax: + 45 65 48 16 15 E-mail: Denmark.ro-clean@desmi.com U.S.A. Office, APPLIED FABRIC TECHNOLOGIES INC PO Box 575, 227 Thorn Ave, Orchard Park, NY 14127 Tel: +1 716 662 0306 Fax: +1 716 662 0306 E-mail: bestboom@afti.com U.K. Office RO-CLEAN DESMI LTD. Unit 24, Shamrock Quay William Street Southampton, SO14 5QL Tel. +44 23 80829751 Fax. +44 23 80339190 E-mail: uk.ro-clean@desmi.com

### Latin America Office RO-CLEAN DESMI LATINOAMERICA S.A. Calle Amagasí del Inca E14-68 y 2° Transversal Edificio RO-CLEAN DESMI - PB Quito-Ecuador Tel.: +593 2 326 1939 Fax: +593 2 326 4844 E-mail: Latinoamerica.ro-clean@desmi.com

Asia Office RO-CLEAN DESMI ASIA 50/F Menara BCA JI. MH. Thammin No. 1 Jakarta 13010 Indonesia Fel: +62 21 2358 4468 Fax: +62 21 2358 4401 =-mail: asia.ro-clean@desmi.con