

# POLLCAT

## - Anti-pollution workboat

The vessel is based on a robust steel catamaran hull, into which an Oil Mop system is built. This enables the POLLCAT to recover oil by simply driving through the slick.

Recovered oil storage, hydraulic power, a clear deck with hydraulic crane make a most versatile tool for many port and terminal operations.

The Oil Mop system can be complemented with skimmers operated from the deck such as the TERMINATOR. Each POLLCAT is custom made according to operator requirements.

Two POLLCATS were used extensively during a three week, 24 hour operation in the "Sea Empress" spill in the United Kingdom with great success!

The Oil Mop system is contained almost completely under deck, allowing the craft to be used for other functions on a daily basis.



The POLLCAT (pollution catamaran) anti-pollution workboats have been supplied to oil companies and terminals around the world.

**POLLCAT**



TECHNICAL DATA

Advantages of POLLCAT:

- 15.5 & 19 m version
- Versatile workboats with highly capable oil spill recovery system
- Clear aft deck
- Optional raised wheelhouse
- Twin engines
- Hydraulic knuckle crane
- Recovered oil storage tanks
- Custom designs
- Stable work platform

	15.5 m POLLCAT	19 m POLLCAT
<b>Material</b>	Steel	Steel
<b>Hull Type</b>	Catamaran	Catamaran
<b>Length</b>	15.5 m / 50ft	19 m / 62ft
<b>Depth</b>	2.15 m / 7.0ft	2.5 m / 8.2ft
<b>Beam Moulded</b>	5.4 m / 18ft	6m / 20ft
<b>Draught light</b>	0.80 m / 3ft approx	1.2 m / 4ft approx
<b>Draught loaded</b>	1.30 m / 4.24ft approx	1.9 m / 6.5ft approx
<b>Speed light</b>	9.0 knots	9.0 knots
<b>Oil Recovery speed</b>	Up to 6 knots	Up to 6 knots
<b>Oil Recovery rate</b>	Up to 50 m <sup>3</sup> hr / 330 UK gpm	Up to 50 m <sup>3</sup> hr / 330 UK gpm
<b>Pumping Capacity</b>	90m <sup>3</sup> hr / 396 US gpm	90 m <sup>3</sup> hr / 396 US gpm
<b>Main engines</b>	2 x 170 hp diesels	2 x 170 hp diesels
<b>Fuel tanks capacity</b>	1,800 litres / 474 US gallons	4,000 litres / 1.056 US gallons
<b>Cruising range</b>	200 nautical miles	500 nautical miles
<b>Recovered oil storage capacity</b>	Up to 50 m <sup>3</sup> hr / 396 US gpm	Up to 50 m <sup>3</sup> hr / 396 US gpm
<b>Crane</b>	600 kg at 7.0m / 1,322 lbs at 23 ft	600 kg at 7.0m / 1,322 lbs at 23 ft
<b>Working deck</b>	52 m <sup>2</sup> / 560ft <sup>2</sup>	68 m <sup>2</sup> / 732ft <sup>2</sup>

**POLLCAT**

**- Contact one of the offices below for further information**



All information is subject to change, and pictures are for illustration purposes only, and not necessarily correct.

**www.ro-cleandesmi.com**



**Head Office**  
RO-CLEAN DESMI A/S  
Hestehaven 61  
DK-5260 Odense S  
Phone: + 45 65 91 02 01  
Fax: + 45 65 48 16 15  
E-mail: Denmark.ro-clean@desmi.com

**U.S.A. Office,**  
APPLIED FABRIC TECHNOLOGIES INC  
PO Box 575,  
227 Thorn Ave,  
Orchard Park, NY 14127  
Tel: +1 716 662 0632  
Fax: +1 716 662 0306  
E-mail: bestboom@afti.com

**U.K. Office**  
RO-CLEAN DESMI LTD.  
Unit 24, Shamrock Quay  
William Street  
Southampton, SO14 5QL  
Tel. +44 23 80829751  
Fax. +44 23 80339190  
E-mail: uk.ro-clean@desmi.com

**Latin America Office**  
RO-CLEAN DESMI LATINOAMERICA S.A.  
Calle Amagasi del Inca E14-68 y 2°  
Transversal  
Edificio RO-CLEAN DESMI - PB  
Quito-Ecuador  
Tel.: +593 2 326 1939  
Fax: +593 2 326 4844  
E-mail: Latinoamerica.ro-clean@desmi.com

**Asia Office**  
RO-CLEAN DESMI ASIA  
50/F Menara BCA  
Jl. MH. Thamrin No. 1  
Jakarta 13010 Indonesia  
Tel: +62 21 2358 4468  
Fax: +62 21 2358 4401  
E-mail: asia.ro-clean@desmi.com